


PRESTOTIG FORCE

Portable TIG DC welding installations





PRESTOTIG FORCE



Modular technology to improve reliability.

Built-in Power Factor Control device in conformance with national standards and to improve efficiency and reduce electrical consumption. Factory fitted with a domestic 16 A plug. Improved compatibility with generators (+/- 20% input voltage variations). Works with extra long primary cables (70 m with 2.5 mm² section). Possibility to use with autonomous cooling system FREEZTIG.

PRESTOTIG FORCE front panel

- A complete welding cycle is straightforward to set: initial, final current, up-slope, downslope, spot time, pre-gas, post-gas, reduced current (4T), pulsed frequency regulation
- High performance for MMA: up to 180 A at 40% at 40 °C
- Program storage capability (30)



- 1 Welding mode (MMA, TIG with PAC striking, TIG with HF striking)
- 2 TIG welding: 2 Times, 4 Times,
- 3 Pulsed DC selection mode
- 4 Remote control Foot pedal control selection
- 5 Programs storage and recall
- 6 Digital display
- 7 Complete welding cycle

FREEZTIG autonomous cooling unit

To increase productivity of vour PRESTOTIG FORCE equipment, add the brand new single phase autonomous cooling unit FREEZTIG.

You will be able to weld with a water cooled torch (100% duty cycle).



One Year Warranty extension

NEW PRESTOTIG FORCE welding sets get a 2 years warranty period as all the professional equipment in the SAF-FRO Range.

From now with your PRESTOTIG FORCE

registration you will get for free an additional one year warranty period, and your PRESTOTIG FORCE equipment will be covered by a 3 years warranty.



Welding consumables

As a selection of the wide SAF-FRO welding consumables range you can see here under TIG rods for the most common applications.

Many other types of steel or alloys are availble. Do not hesitate to consult us.

Applications	Classification	Designation	Diameter	Cat. number
Carbon steels	ER 70S-6 (AWS A 5-18) W42 4 W3Si1 (EN ISO 636-A)	ALTIG SG 2	1.2 mm	W000283327
			1.6 mm	W000283328
			2.0 mm	W000283329
			2.4 mm	W000283330
			3.2 mm	W000283331
Stainless steels	ER 308L (AWS A 5-9) W19 9 L (EN ISO 14343-A)	ALTIG 308L	1.2 mm	W000283419
			1.6 mm	W000283420
			2.0 mm	W000283421
			2.4 mm	W000283422
			3.2 mm	W000283423
3141111633 316613	ER 316L (AWS A 5-9) W19 12 3 L (EN ISO 14343-A)	ALTIG 316L	1.2 mm	W000283455
			1.6 mm	W000283456
			2.0 mm	W000283457
			2.4 mm	W000283458
			3.2 mm	W000283459
Light alloys	ER 5356 (AWS A 5-10) S AI 5356 (EN 18273)	ALTIG AIMg5	1.6 mm	W000283587
			2.0 mm	W000283588
			2.4 mm	W000283589
			3.2 mm	W000283590
			4.0 mm	W000283591



Comply with the EN 61000-3-2/12 standard effective since december 2010, that limits the harmonic

currents produced by equipment connected to public low-voltage systems

PRESTOTIG FORCE Power are PFC Factor Control









SINGLE-PHASE

Technical characteristics

		PRESTOTIG 180 FORCE		PRESTOTIG 220 FORCE			
		MMA	TIG	MMA	TIG		
Single-phase input voltage		230 V +/- 20% 50/60 Hz		230 V +/- 20% 50/60 Hz			
Effective input current		15 A	11 A	16 A	12 A		
Open circuit voltage		50 V		50 V			
Welding curr	Welding current range		5 - 160 A		5 - 220 A		
	30%	-	-	-	-		
5.	35%	160 A	-	-	220 A		
Duty cycle at 40 °C	40%	-	160 A	180 A	-		
ut 10 0	60%	140 A	140 A	150 A	180 A		
	100 %	120 A	130 A	130 A	150 A		
Connector si	Connector size		13 mm				
Protection index		IP 23 S					
Weight	Weight		9.5 kg				
Dimensions		205 x 345 x 460 mm					
F	EN 60974.1	✓		✓			
European standards	EN 60974.10	·	✓		✓		
	EN 61000-3-2/12	✓		✓			
Delivered equipped with		Primary cable, user manual, safety instructions, gas hose, earth cable with clamp (3 m)					

This equipment are designed for industrial and professional use only.

To enden					
To order					
PRESTOTIG 180 FORCE W000382577	PRESTOTIG 220 FORCE W000382578				
Options and accessories					
W000242069					
W000241602					
W000375730					
W000371907					
W000382728					
	W000382577 Options and accessories W0002 W0002 W0003 W0003				

Options and accessories



TIG torches



The new range of PROTIG T NG TIG torches perfectly fit with the high level of quality provided by the PRESTOTIG FORCE professional range.

The adapted models are PROTIG NG 10, 10W, 20 or 30. They come:

- either with trigger as a blade: RL models
- or as a button: EB types.

The EB types are modular as they can be modified with the different type of buttons.

See complete range in the PROTIG NG brochure



PROTIG NG

		PROTIG NG 10 RL S	PROTIG NG 20 RL S	PROTIG NG 30 RL S	PROTIG NG 10W RL S
Cooling			Air		Water
Duty Cycle					250 A @100%
To order	5 m	W000278353	W000278356	W000278358	W000278362
	8 m	W000278355	W000278357	W000278359	W000278363
Cat. number maintenance box		W000306441	W000306442	W000306443	W000306441



		PROTIG NG 10 EB C5B	PROTIG NG 20 EB C5B	PROTIG NG 30 EB C5B	PROTIG NG 10W EB C5B
Cooling		Air			Water
Duty Cycle)				250 A @100%
To order	5 m	W000278394	W000278396	W000278398	W000278402
	8 m	W000278395	W000278397	W000278399	W000278403
m	it. number aintenance box	W000306441	W000306442	W000306443	W000306441

Modular system:

All torches are delivered with a single button module. If you want another control module, order it separatly.









2011-

- 1 Horizontal potmeter W000279370
- 2 Vertical potmeter W000279246
- 3 Doublon button W000279242
- 4 Blade **W000279245**

For potmeter adapt the wiring to the welding machine using the:

- 7 pins plug **W000271826**
- 10 pins plug **W000148887**

In option: Adjustable heads

As an option, adjustable torch bodies are available. Welding in inaccessible locations becomes easier. You have the choice of 2 heads, small and large to be mounted on air cooled body. Choose one body and one head to get a complete torch





Air cooled body - w000279381 Water cooled body - w000279382 (1) Head CITORCH T NG 10 (2) - w000279383 Head CITORCH T NG 20 (3) - w000279384

(1) : duty cycle : 220 A @100% (2) : duty cycle : 125 A @ 35% (3) : duty cycle : 145 A @ 35%

CITOTIG FORCE



PRESTOTIG FORCE offers leading technology in TIG DC welding with a user friendly interface.





PRESTOTIG FORCE

• High quality welding results on carbon and stainless steels.





• For high demanding sectors of activity.













Contacts

BELGIUM

AIR LIQUIDE WELDING BELGIUM SA Z.I. West Grijpen - Grijpenlaan 5 - 3300 TIENEN Tel.: +32 16 80 48 20 - Fax: +32 16 78 29 22

CHINA

AIR LIQUIDE WELDING HANGZHOU SAF-OERLIKON Weld. and Cut. Co. Ltd. 185, Kangtai Road Qianjiang Eco. and Dev. Zone Yuhang District HANGZHOU China 311106 Tel.: +86 21 64 43 89 69 - Fax: +86 21 64 43 58 97

CZECH REPUBLIC

AIR LIQUIDE CZ S.R.O. - Welding and Cutting Podnikatelská 565 - Areál SVUM - 190 11 PRAHA 9 - Búchovice Tel.: +420 274 023 163 - Fax: +420 274 023 233

FRANCE

AIR LIQUIDE WELDING FRANCE 13, rue d' Épluches - CS 10113 Saint-Ouen l'Aumône 95315 CERGY PONTOISE Cedex Tel.: +33 1 34 21 33 33 - Fax: +33 1 34 21 31 30

GERMANY

OERLIKON SCHWEISSTECHNIK GmbH Industriestrasse 12 - D-67304 EISENBERG/PFALZ Tel.: +49 6351 4760 - Fax: +49 6351 476 335

HUNGARY

see address in Romania

FRO-AIR LIQUIDE WELDING ITALIA S.p.A Loc. Casalmenini, 337010 - RIVOLI-VERONESE (VR) Tel.: +39 045 82 91 511- Fax: +39 045 82 91 536

LUXEMBOURG

AIR LIQUIDE WELDING LUXEMBOURG S.A. 5 rue de la Déportation - BP 1385 - L-1415 LUXEMBOURG Tel.: +352 48 54 56 - Fax: +352 48 54 57

MALAYSIA

SAF-OERLIKON MALAYSIA SDN BHD No 10, Jalan TPP 5/1 Taman Perindustrian Puchong - 47100 PUCHONG, SELANGOR Tel.: +603 8060 8638 - Fax: +603 8061 620

NETHERLANDS

AIR LIQUIDE WELDING NETHERLANDS Rudonk 6 B - NL 4824 AJ BREDA Tel.: +31 76 541 00 80 - Fax: +31 76 541 58 96

AIR LIQUIDE WELDING POLSKA - SP. Z.o.o UL. Porcelanowa 10 - 40-246 KATOWICE Tel.: +48 32 609 04 50 - Fax: +48 32 609 04 60

PORTUGAL

AIR LIQUIDE SOLDADURA LDA Rua Dr. António Loureiro Borges, 4-2° Arquiparque Miraflores - 1495-131 ALGÉS Tel: +351 21 41 64 900 - Fax: +351 21 41 69 40

ROMANIA

DUCTIL

Aleea Industriilor Nr 1 - 120224 BUZAU Tel.: +40 238 722 058 - Fax: +40 238 716 861

RUSSIA

AIR LIQUIDE WELDING 17 Vorontsovskaya Str. - 109147 MOSCOW Tel.: +7 495 641 28 98 - Fax: +7 495 641 28 91

SCANDINAVIA

OERLIKON SKANDINAVIEN AB Krossverksgatan 7 - 216 16 LIMHAMN Tel.: +46 (0)40 670 15 00 - Fax: +46 (0)40 670 15 01

SLOVAKIA

AIR LIQUIDE WELDING CENTRAL EUROPE S.R.O. Hlohovecká 6 - 951 41 NITRA - LUŽIANKY Tel.: +421 37 692 4610 - Fax: +421 37 651 28 04

OERLIKON SOLDADURA SA Poligono Industrial la Noria Carretera de Castellon Km-15,500 - 50730 El Burgo de Ebro - ZARAGOZA Tel.: +34 976 10 47 00 - Fax: +34 976 10 42 67

SWITZERLAND

OERLIKON SCHWEISSTECHNIK AG Mandachstrasse 54 - CH 8155 NIEDERHASLI Tel.:+41 44 3076 111 - Fax: +41 44 3076 112

THAILANDE

AIR LIQUIDE WELDING THAILAND Co. Ltd. 40 Moo 6 - Ramindra Road Km 9.5 KHANNAYAO, BANGKOK 10230 Tel.: +66 29 43 2250 - Fax: +66 29 43 2256

UAE

AIR LIQUIDE WELDING MIDDLE EAST FZE Jebel Ali free zone warehouse No. FZS1AH05 P.O. BOX 18734 - Jebel Ali - DUBAI Tel.: +971(0)48861606 - Fax: +971(0)48861608

U.K.

AIR LIQUIDE WELDING Ltd

Low March / London Road - DAVENTRY - Northants NN11 4SD Tel.: +44 1 327 70 55 11 - Fax: +44 1 327 70 13 10

UKRAINE

AIR LIQUIDE WELDING UKRAINE, LIC. Moskovskij Prospect 199 - Office 339 - 61037 KHARKOV Tel.: +38 057 728 08 52- Fax: +38 057 728 08 53

Contacts for other countries:

Air Liquide Welding Export Department Italy

Loc. Casalmenini, 337010 - RIVOLI-VERONESE (VR) Tel.: +39 045 82 91 511- Fax: +39 045 82 91 536

Air Liquide Welding Export Department France

13, rue d'Epluches CS 10113 Saint Ouen l'Aumône 95315 CERGY-PONTOISE Cedex Tel.: +33 1 34 21 33 33 - Fax: +33 1 30 37 19 73

